

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61F 5/48, A61G 7/057	A1	(11) International Publication Number: WO 96/01602 (43) International Publication Date: 25 January 1996 (25.01.96)
(21) International Application Number: PCT/BE95/00066 (22) International Filing Date: 5 July 1995 (05.07.95)	(81) Designated States: US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(30) Priority Data: 9400647 11 July 1994 (11.07.94) BE (71)(72) Applicant and Inventor: HOORENS, Jan [BE/BE]; Bosstraat 19, B-1702 Dilbeek (BE). (74) Agent: CALLEWAERT, Jan; Brusselsesteenweg 108, B-3090 Overijse (BE).	Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> <i>In English translation (filed in Dutch).</i>	

(54) Title: MAT, MORE SPECIFICALLY A MAT FOR LYING ON

(57) Abstract

The invention concerns a mat, more specifically a mat for lying on, characterised in that said mat essentially comprises a three-dimensional fabric or knitted structure with a top layer (1) and a bottom layer (2) connected by a middle layer (3), where the top layer (1) is permeable to moisture and air and the middle layer (3) is permeable to air in such a way that an airflow is possible through said middle layer parallel to the top and bottom layers.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

Mat, more specifically a mat for lying on

The invention concerns a mat, more specifically a mat for lying on, which for example is to be laid on top of a mattress or on a hard surface, such as a floor, with an air-permeable top layer and a bottom layer facing it, separated from each other by a middle layer with an open structure.

According to the invention, the aim is among other things to propose a mat which makes it possible to prevent overheating of those parts of the body in contact with the mat, in particular during hot weather, and more specifically in the case of bed-ridden persons and babies.

Further, the invention also aims to propose a mat which makes it possible to considerably reduce the risk of suffocation or cot death in babies.

To this end, the mat according to the invention comprises a three-dimensional knitted structure, with a middle layer essentially formed by open, relatively rigid threads, more specifically monofilaments, where said threads form part of said three-dimensional knitted structure, and where said threads, more or less evenly distributed, are placed at a certain distance from each other, such that a) said middle layer is more or less incompressible under the weight of a person lying on the top layer, and b) a permanent flow of air is possible between said middle layer and the top layer.

The top and bottom layers are purposefully parallel to each other, and at least 70% of the monofilaments in the middle layer extend more or less perpendicularly to said top and bottom layers, with the remaining portion of the monofilaments being crossed over each other and distributed over the middle layer, in order to prevent said perpendicular monofilaments from

SUBSTITUTE SHEET

turning over or bending under the weight of a person lying on top of the mat.

In an advantageous embodiment of the invention, ~~at least the above-mentioned top layer consists of a~~ knitted structure with meshes having a cross-section of 0.5 mm to 10 mm, and preferably a cross-section of between 2 and 4 mm.

Other features and advantages of the invention will be apparent from the following description of some specific embodiments of a mat for lying on according to the invention; this description is given by way of example and in no way limits the scope of the protection afforded. The reference numbers used below relate to the accompanying drawings.

Fig. 1 is a schematic perspective view of part of a mat for lying on according to a first embodiment of the invention.

Fig. 2 represents a schematic cross-section of part of a mat for lying on according to a second embodiment of the invention.

Fig. 3, on a greater scale, is a schematic perspective view of part of a mat for lying on according to a third embodiment of the invention.

Fig. 4, on an even greater scale, is a schematic detail representation of a special component of the mat according to fig. 3.

In these drawings, the same reference numbers refer to identical or analogous elements.

The mat for lying on presented in the drawings essentially comprises a three-dimensional knitted structure ("Abstandsgewirke" - "face-to-face fabric") with a top layer 1 and a bottom layer 2 separated from each other by a middle layer 3.

At least the top layer 1 and the middle layer 3 are permeable to air, such that an air flow can arise

through the top layer 1 and the middle layer 3, more specifically from the middle layer 3 through the top layer 1. In the middle layer 3, the air flow can occur over the entire mat, in all directions. The continuous ventilation thus generated also ensures that the person lying on top of the mat does not suffer from perspiration.

A baby lying with its face on the mat will always receive a sufficient supply of air through the middle layer 3 and the top layer 1 of the mat, so that the risk of suffocation is virtually excluded and furthermore better temperature regulation is possible.

In the middle layer 3 in particular, the amount of free space is very great in comparison to the material from which said layer is formed, and its volume is preferably at least five times the volume of said material.

In the specific embodiment as represented in fig. 1, the middle layer 3 comprises upright threads 4 woven into those of the top layer 1 and the bottom layer 2. These extend obliquely with respect to the top and bottom layers 1 and 2 which are parallel to each other; said upright threads make the same angle when crossing each other or the two layers, in order to give the middle layer sufficient springiness in a direction perpendicular to it, and at the same to give the required rigidity to ensure that said middle layer is not compressed under the weight of the person lying on top of the mat, thus maintaining the above-mentioned airflow.

To this end, said threads 4 consist for example of relatively rigid monofilaments, preferably with a diameter in the order of 0.01 mm to 0.5 mm, more specifically between 0.09 mm and 0.21 mm.

The middle layer 3 can mostly have a thickness of between 0.1 cm and 1 cm, but preferably between 0.3

SUBSTITUTE SHEET

and 0.6 cm, for example 0.45 cm.

The top layer 1 consists of an open fabric or knitted structure with sufficiently large meshes 5, which ensure the through-flow of air. These preferably have a diameter between 0.5 mm and 10 mm, more specifically between 2 and 4 mm.

The bottom layer 2 is preferably impermeable to moisture. This is particularly important if the mat for lying on is used on a damp surface or as a mattress protector. To this end, the bottom layer 2 can for example consist of a densely woven or knitted structure, on to which a film of plastic or aluminium can be laminated or glued.

The embodiment shown in fig. 2 differs from that in fig. 1 in that the middle layer 3 consists of relatively thick, rigid, upright monofilaments 4, which are not crossed and extend more or less perpendicularly to the top and bottom layers 1 and 2.

Further, the bottom layer 2 consists of a moisture-absorbing material, to the outside of which is glued a plastic film 6 which ensures that the bottom of the mat for lying on is moisture-proof.

In the preferred embodiments according to figs. 1 and 2, the middle layer 3 consists of synthetic monofilaments 4, such as polyester with a diameter of 0.08 mm, while the top layer 1 consists essentially of cotton (detex 100/1) and the bottom layer 2 consists of a polyester fabric (detex 110).

Figs. 3 and 4 relate more specifically to a special embodiment of the three-dimensional knitted structure which according to the invention forms the main part of the mat.

As can be seen, both the top layer 1 and the bottom layer 2 are formed by a very open meshwork, whose meshes 5 are hexagonal.

SUBSTITUTE SHEET

Further, the meshes 5 of both layers are directly opposite each other, and the corresponding sides of said meshes are connected with each other by monofilaments 4, of which at least 70% and preferably at least 90% extend perpendicularly to the two layers 1 and 2 and determine the middle layer 3. The remaining monofilaments are crossed over each other and are evenly distributed over the whole volume of the middle layer 3.

For the sake of clarity, said remaining monofilaments are indicated in fig. 3 by reference number 4'.

As can be clearly seen on this figure, said oblique crossed monofilaments 4' connect one side 1a of each of the meshes 5 of the top layer 1 with a side 2b of the bottom layer 2 located under the side 1b of the top layer lying opposite, and conversely connect the side 1b of the top layer 1 with the side 2a of the bottom layer 2.

In this way, the upright monofilaments 4 are prevented from bending or turning over under the weight of a person lying on top of it, thus making the mat more or less incompressible under such a weight.

Furthermore, in order to obtain a stable whole, the monofilaments 4 and 4' form part of the three-dimensional knitted structure itself, and are in a way woven into the sides of the layers 1 and 2 which delimit the meshes 5. In this way the three layers 1, 2 and 3 are formed in a single knitting pass.

Also, the sections of the monofilaments 4 and 4' which are woven into the top and bottom layers 1 and 2 are completely sunk into said layers, such that the outsides of both these layers are nearly completely smooth.

This is illustrated in fig. 4, which is a schematic representation of part of a side of one of the

SUBSTITUTE SHEET

meshes of the top layer 1 and of part of the corresponding side underneath it in the bottom layer 2.

Further, at least the top layer 1 consists essentially of microfilaments which themselves are known. For the sake of clarity, however, these microfilaments are not shown in fig. 4.

In the embodiment according to figs. 3 and 4, the three-dimensional knitted structure corresponds to the following specifications:

- top layer 1: microfilaments of polyester dtex 110f 128 x 3; "jet-tex" (trademark of Hoechst)
- middle layer 3: monofilaments of polyester with diameter of 0.16 mm
- bottom layer 2: polyester dtex 167 f 32 x 1.

In some cases, means may be easily provided to obtain a forced air flow through the top layer 1 via the middle layer 3. This can be done for example by connecting a dismountable fan on one of the edges of the mat by means of a suitable nozzle which extends over the full length of the side and is attached to it by means of a clamp system without compressing the mat.

In addition to the above-mentioned advantages, the mat according to the invention has the further advantage that it is easy to wash, due in particular to the more or less continuous free space of the middle layer 3.

Further, this mat remains free of house mites, thanks to the above-mentioned continuous flow of air in the middle layer 3, the relatively low temperature which is maintained and the absence of perspiration moisture, making it ideal for people who are allergic to these mites.

Further, the three-dimensional knitted structure shown in fig. 3 is very easy to see through, thanks to the meshes lying opposite each other in the top

SUBSTITUTE SHEET

and bottom layers, making it easy to check the permeability to air.

These different types of three-dimensional knitted structure can be manufactured by the "Karl Mayer" company using a machine of the type "RD-6".

The invention is of course in no way limited to the embodiments described above and shown in the accompanying drawings; other variants can be considered as regards the choice of material used for the knitted structure and the dimensions of same.

Further, the mat can for example form part of the top of a mattress, being removably attached to the mattress. The thickness and rigidity of the mat can also be varied in function of the weight of the person lying on top of it.

On at least one of the layers 1 or 2, but preferably on the top layer 1, an extra molton layer may be provided, such that the air-permeability of the top layer is scarcely affected.

Finally, the invention is not limited to a mat for lying on but can be applied wherever there are problems of cooling, air permeability, oxygen supply, etc., such as for horse blankets or saddle cloths.

SUBSTITUTE SHEET

CLAIMS

1. Mat, more specifically a mat for lying on, with a top layer (1) which is permeable to air and with a bottom layer (2) facing it, said layers being separated from each other by a middle layer (3) with an open structure, characterised in that said mat essentially comprises a three-dimensional knitted structure, whose middle layer (3) is essentially formed by upright, relatively rigid threads, more specifically monofilaments (4) and (4') which form part of said three-dimensional knitted structure and which extend at a certain distance from each other, more or less evenly distributed, such that firstly said middle layer (3) is nearly incompressible under the weight of a person lying on the top layer (1), and secondly a permanent flow of air is possible through said middle layer (3) and top layer (1).

2. Mat according to claim 1, characterised in that the top layer (1) and the bottom layer (2) are parallel to each other and that at least 70% of the monofilaments (4) in the middle layer (3) extend more or less perpendicularly to said top layer (1) and bottom layer (2), with the remaining portion of the monofilaments (4') being crossed over each other and distributed over the middle layer, in order to prevent said perpendicular monofilaments (4) from turning over or bending under the weight of a person lying on top of the mat.

3. Mat according to claim 1 or 2, characterised in that the volume of free space in the middle layer (3) is at least five times the volume of the monofilaments (4) and (4').

4. Mat according to one of claims 1 to 3, characterised in that the monofilaments (4) and (4') have a diameter of between 0.01 mm and 0.5 mm, and preferably

SUBSTITUTE SHEET

between 0.09 mm and 0.21 mm.

5. Mat according to one of claims 1 to 4, characterised in that said middle layer (3) has a thickness of between 0.1 cm and 1 cm, and preferably between 0.3 cm and 0.6 cm.

6. Mat according to one of claims 1 to 5, characterised in that at least said top layer (1) consists of a knitted structure with meshes (5) of 0.5 mm to 10 mm in cross-section and preferably between 2 and 4 mm cross-section.

7. Mat according to one of claims 1 to 6, characterised in that the portion of the monofilaments that form part of the top layer (1) and bottom layer (2) are sunk into said layers.

8. Mat according to one of claims 1 to 7, characterised in that at least the top layer (1) consists essentially of microfilaments.

9. Mat according to one of claims 1 to 8, characterised in that a molton layer is provided on at least one of the mat's outside surfaces.

10. Mat according to one of claims 1 to 9, characterised in that a moisture-proof film (6) is applied to the bottom.

11. Mat according to one of claims 1 to 10, characterised in that it forms part of a mattress and is attached to same in a removable manner.

12. Mat according to one of claims 1 to 11, characterised in that means are provided for creating a forced air flow through the top layer (1) via the middle layer (3).




Fig. 1




Fig. 2




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

Int: nal Application No
PCT/BE 95/00066

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A61F5/48 A61G7/057

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 A61F A61G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE,A,41 11 743 (FORSCHUNGSINSTITUT FÜR TEXTILTECHNOLOGIE CHEMNITZ GMBH) 8 October 1992 see the whole document ---	1-12
A	EP,A,0 261 904 (STANDARD TEXTILE COMPANY INC.) 30 March 1988 see column 3, line 7 - line 25; figures ---	1-12
A	US,A,4 695 496 (LEE) 22 September 1987 see column 6, line 1 - line 13; figure 5 ---	1-12
A	CH,A,455 142 (PFISTER) 28 June 1968 see column 2, line 19 - line 22; figures ---	1-12
A	DE,U,91 12 275 (ZIEGLER) 16 January 1992 see page 4, line 21 - line 30 ---	1-12
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *&* document member of the same patent family

Date of the actual completion of the international search

20 October 1995

Date of mailing of the international search report

17. 11. 95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

Godot, T

INTERNATIONAL SEARCH REPORT

Internal Application No
PCT/BE 95/00066

PCT/BE 95/00066

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US,A,3 691 570 (GAINES ET AL.) 19 September 1972 ---	
A	FR,A,2 616 320 (CHERENCE) 16 December 1988 -----	

INTERNATIONAL SEARCH REPORT

International Application No
PCT/BE 95/00066

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE-A-4111743	08-10-92	NONE	
EP-A-0261904	30-03-88	US-A- 4961982	09-10-90
US-A-4695496	22-09-87	NONE	
CH-A-455142		NONE	
DE-U-9112275	16-01-92	NONE	
US-A-3691570	19-09-72	NONE	
FR-A-2616320	16-12-88	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.